

Intrinsically Safe Permissible Polymer Dual-Light™ Flashlights

Flashlight



Floodlight



Dual-Light



TECHNOLOGY



These Dual-Light™ flashlights are cETLus, ATEX, IECEx, MSHA and INMETRO listed Intrinsically Safe Permissible. They each use a CREE® LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Power comes from 3AA batteries (not included).

**INTRINSICALLY SAFE
PERMISSIBLE**



120 Flashlight
Lumens

120 Floodlight
Lumens

240 Dual-Light™
Lumens

- cETLus, ATEX, IECEx, MSHA and INMETRO listed Intrinsically Safe Permissible
- Flashlight/floodlight/Dual-Light™
- Beam distance rated at 170 meters
- Engineered polymer housing



XPP-5422B

XPP-5422G



GAVMANAK
0414-622-007

gavmanak@bigpond.com

XPP 5422 series



Intrinsically Safe Permissible Polymer Dual-Light™ Flashlights

High-efficiency deep parabolic reflector

FEATURES

- Flashlight – floodlight – Dual-Light™
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-Light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- Non-slip grip
- Dual body switches
- Dustproof / Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries (not included)
- Available in black & green
- Limited Lifetime Warranty

SPECIFICATIONS

- Lumens: flashlight-120, floodlight-120, dual-light-240
- Run-time: flashlight-17.5 hrs, floodlight-17.5 hrs, dual-light-4.5 hrs
- Beam distance: 170 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 6.9oz

FL 1 STANDARD		
120 LUMENS	17h 30min	170m
7250cd	2m	1m

INCLUDED

- Flashlight with built-in pocket/belt clip
- Removable lanyard

SAFETY RATING

cETLus, ATEX, IECEx, MSHA and INMETRO listed Intrinsically Safe Permissible



Built in pocket/belt clip



Dual body switches



Wide-beam floodlight



GAVMANAK
0414-622-007

gavmanak@bigpond.com