

NIGHT STICK®

X-Series Intrinsically Safe Dual-Light™ Flashlight

Flashlight



Floodlight



Dual-Light



TECHNOLOGY



This Dual-Light™ Flashlight is cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. The XPP-5422GX uses a CREE® LED rated at 210 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 187 meters. A 130 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. Power comes from 3 AA premium batteries (not included).

INTRINSICALLY SAFE

210 Flashlight
Lumens

130 Floodlight
Lumens

285 Dual-Light™
Lumens



- cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- Beam distance rated at 187 meters
- Engineered polymer housing

XPP 5422GX



GAVMANAK
0414-622-007

NIGHTSTICK

XPP 5422GX



X-Series Intrinsically Safe Dual-Light™ Flashlight

FEATURES

- cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- Flashlight – floodlight – Dual-Light™
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-Light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- Non-slip grip
- Dual body switches
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries (not included)
- Limited Lifetime Warranty*



Built in pocket/belt clip



Dual body switches



Wide-beam floodlight

Model	UPC 0 17398
XPP-5422GX	80584 1

SPECIFICATIONS

- Lumens: flashlight-210, floodlight-130, dual-light-285
- Run-time: flashlight-14 hrs, floodlight-20 hrs, dual-light-10 hrs
- Beam distance: 170 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 6.9oz

FL 1 STANDARD		
210 LUMENS	14h	187m
7970cd	2m	1m

INCLUDED

- Flashlight with built-in pocket/belt clip
- Removable lanyard

SAFETY RATING

cETLus, ATEX, and IECEx listed Intrinsically Safe
Patent 7,738,229

ID 4003544 INTRINSICALLY SAFE SECURITE INTRINSEQUE CLASS I DIV 1 GRPS A-D T3 CLASS II & III DIV 1 GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T3 Ga CLASS I ZONE 0 Ex ia IIC T3 Ga ⊕ I M 1 Ex ia op ia I Ma ⊕ II 1 G Ex ia op is IIC T3 Ga	XPP-5422GX 0359 Ex ia op is I Ma Ex ia op is IIC T3 Ga Intertek ITS 13 ATEX27837X IECEX ITS 16 0667X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AA Alkaline
	Conforms to: ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11 ANSI/ISA 60079-26
SEE INSTRUCTION MANUAL VOIR MANUEL	



GAVMANAK

0414-622-007